



LIOPUR PFL 2315

Aqueous, aliphatic polyurethane dispersion

LIOPUR PFL 2315 is an almost solvent and TEA-free polyurethane dispersion based on a polyester / polycarbonate combination.

The product finds its use in both pigmented and transparent systems.

FIELD OF APPLICATION

LIOPUR PFL 2315 forms transparent films which are tack-free and offer good surface hardness after air-drying /forced drying. Due to its high abrasion resistance and excellent chemical resistance, LIOPUR PFL 2315 is distinguished for 2-pack parquet floor varnishes and furniture coatings. 2-pack formulations based on LIOPUR PFL 2315 are easy to handle and can be safely used by professionals and for do-it-yourself applications.

HIGHLIGHTS

- universally applicable
- high chemical resistance
- high abrasion resistance
- good miscibility, e.g. in combination with our LIOCRYL acrylic dispersions
- good surface hardness
- suitable for DIY



PROPERTIES AND TECHNICAL DATA

non volatile content	35 +/-2 %
viscosity/ 23° C	20 - 500 m*Pas
MFFT	appr. 20 °C
pH-value/ 20° C	7,0 – 9,0
visual appearance	transparent to slightly colloidal



SAMPLING

Liopur PFL 2315 is an established product and samples are easily available.

CONTACT



If you are interested in more information about our products (Guide Formulations, Datasheets), please contact your Cathay Industries Territory Manager:

www.cathayindustries.com.au